



TRS - RUTASEAL® Chloroprene Metric

Suitable for holes in materials of 0,5 - 4mm thickness.

Comply with 'Det Norske Veritas' rules for Classification of Ships, High Speed & Light Craft and 'Det Norske Veritas' Offshore Standards.

- Quick and simple assembly without the use of tools
- Resistant to chemicals
- Ageing and Weatherproof

Specification

INFORMATION_KLIKSEAL	(1) Unstressed material.
MATERIAL	Chloroprene
INGRESS PROTECTION	IP67 acc. to EN 60529
TEMPERATURE RANGE	-30°C....+100°C (1)
COLOUR	Black RAL 9005
TEST STANDARD	EN60670-1:2005+A1:2013
SEMKO REPORT	2002133 2100897 (M12-F, M16-F & M63)
DNV-GL TYPE APPROVAL	TAE00002G6

Variants

E-NUMBER	SIZE	FOR CABLE Ø MM	A MM	B MM	D MM	H MM	H1 MM	PCS/PACK
1458253	M12	4 - 7	12.5	0,5-2	20	12,7	5.4	50
1458254	M16	5 - 9	16.5	1-4	21	18	10.5	50
1458255	M20	8 - 13	20.5	1-4	25,5	20	12.7	50
1458256	M25	11 - 17	25.5	1-4	30,5	21,6	14.5	50
1458257	M32	15 - 20	32.5	1-4	38,5	24,8	17.5	25
1458258	M40	19 - 28	40.5	1-4	48,5	30	20.4	25
1458259	M50	27 - 35	50.5	1-4	60,5	35	23.9	10
1458260	M63	34 - 45	63.5	1-4	73,5	40	28.9	5