



Conduit CYL - Black

Polyamide 6 standard applications

- For machine building and installation industries material.
- High-grade, specially formulated polyamide 6 characteristics.
- Very good flexibility.
- Good impact strength also at low temperatures and dry conditions.
- Temperature range -40°C ... $+105^{\circ}\text{C}$ continuous, $+160^{\circ}\text{C}$ short-term
- Self-extinguishing.
- Free from halogens and cadmium.

* lowest recommended bending radius for static (fixed) installation.

Specification

INFORMATION_KLIKSEAL

MATERIAL	Polyamide PA6
TEMPERATURE RANGE	-40°C ... $+105^{\circ}\text{C}$
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	PROFILE	SIZE	Ø D MM	Ø DI MM	STAT R MM*	PCS/PACK
1410800	CYLT-07B.50	T	NW 7	10	6,2	15	50
1410810	CYLT-10B.50	T	NW 10	13	9,6	20	50
1410820	CYLT-12B.50	T	NW 12	15.8	12	30	50
1410830	CYLT-17B.50	T	NW 17	21.2	16,2	40	50
1410840	CYLG-23B.50	G	NW 23	28.5	21,9	45	50
1410850	CYLG-29B.50	G	NW 29	34.5	27,6	55	50
1410860	CYLG-36B.30	G	NW 36	42.5	36	60	30
1410870	CYLG-48B.30	G	NW 48	54.5	47	70	30