



Conduit Multi XVCS1H - Black

Infrastructure

- For track side applications.
- Outer layer: high-grade, specially formulated polyamide 6.
- Inner layer: specially modified polyolefin characteristics.
- Very long life time, >20 years.
- Excellent cold temperature performance
- Easy layouting through: - high conduit ductility and formability
- Low friction inner layer facilitates cable insertion.
- Very good resistance to ultra violet rays and atmospheric corrosion.
- Very good mechanical strength while simultaneously highly flexible
- Impermeable to water and steam.
- Temperature range -50°C ... +90°C continuous, +120°C short-term.

* lowest recommended bending radius for static (fixed) installation.

Specification

INFORMATION_KLIKSEAL

MATERIAL	Outer layer: Polyamide 6, Inner layer: Polyolefin
TEMPERATURE RANGE	-50°C....+90°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	PROFILE	SIZE	Ø D MM	Ø D1 MM	STAT R MM*	PCS/PACK
1406001	XVCS1H-10BG	T	NW 10	13	9.2	25	50
1406002	XVCS1H-12BG	T	NW 12	15.5	11.7	30	50
1406003	XVCS1H-17BG	G	NW 17	21	15.2	40	50
1406004	XVCS1H-23BG	G	NW 23	28.4	21.7	50	50
1406005	XVCS1H-29BG	G	NW 29	34.3	27.5	60	50
1406006	XVCS1H-36BG	G	NW 36	42.2	35.8	70	30
1406007	XVCS1H-48BG	G	NW 48	54.3	46.8	80	30