



Junction Boxes Combi 1010 IP66

Specification

INFORMATION_KLIKSEAL

- 14 knockouts for Cable Glands M20 up to M32. (5x M25/M32, 2x M20, 3x M20/M25 at the side and 2x M25/M32, 2x M20/M25 in the base)
- 4 captive quick-release lid screws
- Sealable lid
- Impact resistant
- UV-resistant
- Incl. Cableentries (Membrane Screw) and Locknut, 2x M25 and 1x M32

MATERIAL	Polypropylen, reinforced glass fibre
INGRESS PROTECTION	IP66/67 acc.to EN 60529
TEMPERATURE RANGE	-30°C....+100°C
FLAME PROTECTION	Glow wire test 750°C acc. to EN 60695-2-11
HALOGEN-FREE	Yes

Variants

E-NUMBER	TERMINAL BLOCK	WIDTH MM	HEIGHT MM	LENGTH MM	COLOUR	PCS/PACK
1438585	-	140	82	140	White	2
1438586	-	140	82	140	Lightgrey RAL7035	2
1438583	-	140	82	140	Black	2
1438581	5x10mm ²	140	82	140	White	2
1438588	5x10mm ²	140	82	140	Lightgrey RAL7035	2
1438587	5x10mm ²	140	82	140	Black	2

