



Junction Boxes Combi 308 IP66

Specification

INFORMATION_KLIKSEAL

- Integrated M20x1,5 threads for cable glands, locknuts not necessary
- 4 quick-release lid screws in the cover
- 8 elastic self-sealing cable inlets
- Impact resistant
- UV-resistant
- Including mounting clip for snap-on fixing

MATERIAL	Polypropylen, reinforced glass fibre
MEMBRANE	TPE
INGRESS PROTECTION	IP66 acc.to EN 60529
TEMPERATURE RANGE	-30°C....+100°C
FLAME PROTECTION	Glow wire test 750°C acc. to EN 60695-2-11
HALOGEN-FREE	Yes

Variants

E-NUMBER	FOR CABLE Ø MM	TERMINAL BLOCK	WIDTH MM	HEIGHT MM	LENGTH MM	COLOUR	PCS/PACK
1438560	3 - 12	-	85	51	85	White	5
1438562	3 - 12	-	85	51	85	Lightgrey RAL7035	5
1438561	3 - 12	-	85	51	85	Black	5
1438565	3 - 12	5x2,5mm ²	85	51	85	White	5
1438567	3 - 12	5x2,5mm ²	85	51	85	Lightgrey RAL7035	5
1438566	3 - 12	5x2,5mm ²	85	51	85	Black	5