



## Junction Boxes Combi IP68 Gel

- Mixing bag solution allows for a professional and clean sealing of the box as well as an easy removal of the filling material, plastic sprue allows for easy sealing
  - Filling material consolidates after a few minutes
  - Delivery includes: Combi Junction box, plastic bag with fluid, plastic sprue and stop end
- 
- Junction box including gele, ensures a high life expectancy, even under permanent influence of moisture, ideal for ports and shipyards, car wash plants, tunnels and flooding areas
  - IP68 up to a water depth of up to 15 meters and 170 hours according to DIN EN 60529
  - Usable at temperatures between -30°C and +100°C (intermittently to approx. +120°C)

### Specification

<b>MATERIAL</b>	Polypropylen, reinforced glass fibre
<b>GEL</b>	Polyorganosiloxane
<b>MEMBRANE</b>	TPE
<b>INGRESS PROTECTION</b>	IP68 - 1,5 bar (170h)
<b>TEMPERATURE RANGE</b>	-30°C....+100°C (-5°C....+60°C during installation)
<b>FLAME PROTECTION</b>	Glow wire test 750°C acc. to EN 60695-2-11
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	FOR CABLE Ø MM	WIDTH MM	HEIGHT MM	LENGTH MM	COLOUR	PCS/PACK
1438568	3 - 12	85	51	85	Lightgrey RAL7035	1
1438578	3 - 17	110	66	110	Lightgrey RAL7035	1
1438589	14 Knockouts M20-M32	140	82	140	Lightgrey RAL7035	1