



MCB 1-pole type C

- Semko approved - Ref no 1621033
- Function of isolation acc. to IEC 60947-2
- Contact position indication
- Fork / Pin connection for Busbars
- D-characteristic on request

Specification

RATED VOLTAGE	230/400V AC
RATED SHORT-CIRCUIT CAPACITY ICN	10kA
RATED FREQUENCY	50/60Hz
ENERGY LIMITING CLASS	3
ELECTRO-MECHANICAL ENDURANCE	8000 cycles
CONNECTION CAPACITY	1 - 25 mm ²
FASTENING TORQUE	2,0 Nm
INSTALLATION	DIN rail 35 mm
TEMPERATURE RANGE	-5°C.....+40°C
INGRESS PROTECTION	IP20
STANDARDS	EN 60898-1:2003+A1+A11+A12+A13

Variants

E-NUMBER	ARTICLE NO.	KARAKTERISTIK	RATED CURRENT A	PCS/PACK
2146422	RSC-101	C	1	12/120
2146424	RSC-102	C	2	12/120
2146426	RSC-103	C	3	12/120
2146428	RSC-104	C	4	12/120
2146432	RSC-106	C	6	12/120
2146436	RSC-110	C	10	12/120
2146438	RSC-113	C	13	12/120
2146440	RSC-116	C	16	12/120
2146442	RSC-120	C	20	12/120
2146444	RSC-125	C	25	12/120
2146446	RSC-132	C	32	12/120
2146448	RSC-140	C	40	12/120
2146450	RSC-150	C	50	12/120
2146452	RSC-163	C	63	12/120