



MCB 2-pole Type C

- Semko approved - Ref no1621033
- Function of isolation acc. to IEC 60947-2
- Contact position indication
- Fork / Pin connection for Busbars
- D-characteristic on request.

Specification

RATED VOLTAGE	230/400V AC
RATED SHORT-CIRCUIT CAPACITY ICN	10kA
RATED FREQUENCY	50/60Hz
ENERGY LIMITING CLASS	3
ELECTRO-MECHANICAL ENDURANCE	8000 cycles
CONNECTION CAPACITY	1 - 25 mm ²
FASTENING TORQUE	2,0 Nm
INSTALLATION	DIN rail 35 mm
TEMPERATURE RANGE	-5°C.....+40°C
INGRESS PROTECTION	IP20
STANDARDS	EN 60898-1:2003+A1+A11+A12+A13

Variants

E-NUMBER	ARTICLE NO.	KARAKTERISTIK	RATED CURRENT A	PCS/PACK
2146462	RSC-201	C	1	6/60
2146464	RSC-202	C	2	6/60
2146466	RSC-203	C	3	6/60
2146468	RSC-204	C	4	6/60
2146472	RSC-206	C	6	6/60
2146476	RSC-210	C	10	6/60
2146478	RSC-213	C	13	6/60
2146480	RSC-216	C	16	6/60
2146482	RSC-220	C	20	6/60
2146484	RSC-225	C	25	6/60
2146486	RSC-232	C	32	6/60
2146488	RSC-240	C	40	6/60
2146490	RSC-250	C	50	6/60
2146492	RSC-263	C	63	6/60