

















3-pole Connection cable black Dca

Halogen-free 1,5mm² & 2,5mm² (Dca)

Specification

RATED VOLTAGE	250 V
RATED CURRENT	16A 1,5mm ² / 20A 2,5mm ²
CODING CONTACT CONFIGURATION	1 - 3-pole Mains
MATERIAL ISOLATION	PA
MATERIAL TERMINALS	Brass
CABLE TYPE	H05Z1Z1-F
PROTECTIVE CONDUCTOR	Yellow/Green
INGRESS PROTECTION	IP20, IP40 when plugged
MAX. AMBIENT TEMPERATURE	+70°C
COLOUR	Black
SHEAT COLOUR	Black
BURNING BEHAVIOR CPR	Dca-s2,d2,a1
HALOGEN-FREE	Yes

Variants

E-NUMBER	DIMENSION N X MM ²	CABLE LENGTH M	PCS/PACK	BVB
1278079	3G1,5	1	1	
1278080	3G1,5	2	1	
1278081	3G1,5	3	1	
1278082	3G1,5	4	1	
1278083	3G1,5	5	1	
1278084	3G1,5	6	1	
1278085	3G1,5	7	1	
1278086	3G1,5	8	1	
1278087	3G1,5	9	1	
1278088	3G1,5	10	1	
1278979	3G2,5	1	1	
1278980	3G2,5	2	1	
1278981	3G2,5	3	1	
1278982	3G2,5	4	1	
1278983	3G2,5	5	1	