



3-pole Plugs & Sockets black

Specification

RATED VOLTAGE	250 V
RATED CURRENT	20A
CODING CONTACT CONFIGURATION	1 - 3-pole Mains
MATERIAL ISOLATION	PA
MATERIAL TERMINALS	Brass
INGRESS PROTECTION	IP20, IP40 when plugged
MAX. AMBIENT TEMPERATURE	+70°C
COLOUR	Black
HALOGEN-FREE	Yes

Variants

E-NUMBER	DESCRIPTION	CONNECTION CAPACITY	CABLE ENTRIES MM	PCS/PACK
1278006	3-pole Socket with screw connection 1,5mm ²	0,5mm ² - 4,0mm ²	7,5 - 8,5	1
1278007	3-pole Plug with screw connection 1,5mm ²	0,5mm ² - 4,0mm ²	7,5 - 8,5	1
1278010	3-pole Socket with screw connection 2,5mm ²	0,5mm ² - 4,0mm ²	9,5 - 10,5	1
1278011	3-pole Plug with screw connection 2,5mm ²	0,5mm ² - 4,0mm ²	9,5 - 10,5	1
1278014	3-pole Socket with screwless connection 2,5mm ²	0,5mm ² - 2,5mm ²	7,5 - 10,5	1
1278015	3-pole Plug with screwless connection 2,5mm ²	0,5mm ² - 2,5mm ²	7,5 - 10,5	1