



Sealing insert for flat cables Metric

Sealing insert for chemfered cables.

Assembled in "PERFECT" metric plastic- and metal cable glands.

Suitable for Cable Glands from the E-no. series below.

Polyamide: 1476103-, 05-09, 1476113-18, 1476123-29, 1475903-08, 1476163-68, 1475913-18, 1476172-77, 1476262-64

Nickel-plated brass: 1476003-08, 1476013-18, 1475703-08, 1473203-09, 1473213-19

Stainless Steel: 1475056-61

Protection grade:

IP66 if the outer dimensions of the cable match the slot dimensions "C".

IP54 for cable dimensions between "C" & "C min" in table below.

Article	Polyamide "C min"	Ni-plated Brass / Stainless Steel "C min"
1466623	2 x 8	2 x 9
1466624	2 x 10	2 x 11
1466625	3 x 12	3 x 13
1466626	3 x 19	3 x 17
1466627	4 x 23	4 x 24
1466628	6 x 32	5 x 33

Specification

MATERIAL	TPE TPS
TEMPERATURE RANGE	-30°C....+100°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

E-NUMBER	SIZE	C	DA MM	H MM	PCS/PACK
1466623	M20	5 x 12	15.1	7,5	50
1466624	M25	6 x 16,3	19.8	9,3	50
1466625	M32	9 x 20	25.1	12,5	25
1466626	M40	10 x 27	32.3	15	10
1466627	M50	13 x 34	41	17	5
1466628	M63	15 x 45	54	18	5