



Cable Gland Brass "WADI-zero" IP66/IP67/IP69

- material of the sealing insert fulfills superior claims on fire protection against UL 94 V-0 and EN 45545-2, R22: HL3 / R23: HL3
- large-area sealing protects the cable
- increased anchorage with high retention
- wide sealing and clamping range
- the inner sealing ring can be removed easily for larger cables
- material of the sealing insert fulfills superior claims on fire protection against UL 94 V-0 and EN 45545-2, R22: HL3 / R23: HL3
- high UV, ozone and weather resistance

Specification

MATERIAL	Brass nickel plated (CuZn39Pb3)
SEALING RING	TPE TPS
O-RING	NBR
INGRESS PROTECTION	IP66, IP67, IP69
TEMPERATURE RANGE	-60°C.....+100°C
COLOUR	Brass nickel plated
TEST STANDARD	EN 62444, EN 45545-2
HALOGEN-FREE	Yes

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	D1 MM	D2 MM	H MM	SW1 MM	SW2 MM	PCS/PACK
K160-1012-00	M12x1,5	3 - 8	6.5	8	5	25.5	16	16	100
K160-1016-00	M16x1,5	5 - 10,5	7	10.5	7.5	31.5	20	20	100
K160-1020-00	M20x1,5	8 - 15	8	15	10.5	33	25	25	50
K160-1025-00	M25x1,5	12,5 - 20,5	8	20.5	15.5	35.5	32	32	50
K160-1032-00	M32x1,5	17 - 25,5	9	25.5	20.5	40.5	36	36	25
K160-1040-00	M40x1,5	24 - 33	9	33	29	43	45	45	10
K160-1050-00	M50x1,5	31 - 42	10	42	37.5	47.7	55	55	5
K160-1063-00	M63x1,5	40 - 53	10	53	46	53	70	70	5