

Cable Gland Polyamide IP66/68 Ex i long thread Metric

Ex-i for non armoured cable

Incl. connection thread gasket

Specification

MATERIAL	Polyamide
SEALING RING	EPDM
SEALING RING CONNECTION THREAD	EPDM
INGRESS PROTECTION	IP66, IP68 - 5 bar (30 min.)
TEMPERATURE RANGE	-40°C....+75°C (M12 +15°C....+65°C)
COLOUR	Blue RAL 5012/Black RAL 9005
CATEGORY / ZONE	2 G (1,2) 2 D (21,22)
EQUIPMENT GROUP	II
TYPE OF PROTECTION	Ex eb, Ex tb
CERTIFICATIONS	IECEx, ATEX

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW MM	E MM	PCS/PACK
1467701	ESKE/1-L-I 12	M12x1,5	3 - 6	15	40	16	18	50
1467702	ESKE/1-L-I 16	M16x1,5	4,5 - 9	15	43	20	22	50
1467703	ESKE/1-L-I 20	M20x1,5	7 - 13	15	48	24	27	50
1467704	ESKE/1-L-I 25	M25x1,5	10 - 17	15	51	29	32	50
1467705	ESKE/1-L-I 32	M32x1,5	13 - 21	15	53	36	40	25
1467706	ESKE/1-L-I 40	M40x1,5	17 - 28	18	71	46	51	10
1467707	ESKE/1-L-I 50	M50x1,5	23 - 35	18	76	55	61	4
1467708	ESKE/1-L-I 63	M63x1,5	34 - 48	18	81	68	75	1

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö