Blyfri



Locknut EMC Lead-Free Metric

Lead-Free

- For secure tightening of EMC-cable glands, to cut through paint layers or powder coatings ensuring optimal contact for quipotential bonding, increased vibration resistance
- Lead-Free

Specification

MATERIAL	Brass nickel plated (CuZn21Si3P)
TEMPERATURE RANGE	-60°C....+200°C
COLOUR	Brass nickel plated
HALOGEN-FREE	Yes

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

E-NUMBER	ARTICLE NO.	INTERNAL THREAD	H MM	H1 MM	SW1 MM	E1 MM	PCS/PACK
1473271	50.212YPOT	M12x1,5	3.5	2.8	15	17	100
1473272	50.216YPOT	M16x1,5	3.5	2.8	19	22	100
1473273	50.220YPOT	M20x1,5	3.7	3	24	27	100
1473274	50.225YPOT	M25x1,5	4.2	3.5	30	35	50
1473275	50.232YPOT	M32x1,5	4.7	4	36	41	50
1473276	50.240YPOT	M40x1,5	5.7	5	46	53	50
1473277	50.250YPOT	M50x1,5	5.7	5	60	69	10
1473278	50.263YPOT	M63x1,5	6.7	6	70	80	10

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö