

Blind Plug CLEAN Plus

1.4404 / AISI 316L

The blind plugs CLEAN Plus allow any holes in housings not required for cable entries to be hygienically and effectively sealed. The blind plugs in stainless steel are approved in accordance with EHEDG.

Specification

MATERIAL	Stainless Steel 1.4404/AISI 316L
O-RING	TPU
INGRESS PROTECTION	IP68 - 15 bar, IP69K
TEMPERATURE RANGE	-40°C....+85°C

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

ARTICLE NO.	CONNECTION THREAD	L MM	H MM	SW1 MM	E1 MM	PCS/PACK
BSM12VAcp	M12x1,5	5	15	14	16.5	5
BSM16VAcp	M16x1,5	6	17	18	20.4	5
BSM20VAcp	M20x1,5	6.5	18.5	22	24	5
BSM25VAcp	M25x1,5	7.5	20.5	27	29.4	5
BSM32VAcp	M32x1,5	8	22	34	37.4	5
BSM40VAcp	M40x1,5	8	23	40	44.4	4
BSM50VAcp	M50x1,5	10	26	50	54.4	1
BSM63VAcp	M63x1,5	10	27	65	68.4	1

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö