



Cable Gland Cleanplus Metric

Specification

MATERIAL	Pressure screw in Stainless steel 1.4404/AISI 316L, Double nipple in Stainless steel 1.4305/AISI 303
SEALING RING	Silicone HTS
INGRESS PROTECTION	IP68 up to 15 bar, IP69
TEMPERATURE RANGE	-55°C....+180°C
COLOUR	Stainless Steel
CERTIFICATIONS	EHEDG

Variants

ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	FOR CABLE Ø MM EHEDG	L MM	H MM	H1 MM	SW1 MM	SW2 MM	E2 MM	PCS/PACK
CP212VA4HTS	M12x1,5	3,5 - 4,5	3,5 - 4,5	7	25	16	11	17	19,5	5
CP212VA5HTS	M12x1,5	4,0 - 5,0	4,0 - 5,0	7	25	16	11	17	19,5	5
CP212VA6HTS	M12x1,5	4,0 - 6,5	5,0 - 6,0	7	25	16	11	17	19,5	5
CP212VA7HTS	M12x1,5	5,0 - 7,5	6,0 - 7,0	7	25	16	11	17	19,5	5
CP216VA8HTS	M16x1,5	5,5 - 7,5	5,5 - 7,5	9	29	17	15	21	23,5	5
CP216VA9HTS	M16x1,5	6,5 - 8,5	6,5 - 8,5	9	29	17	15	21	23,5	5
CP220VA9HTS	M20x1,5	6,5 - 9,5	7,5 - 9,5	9	33	21	19	24	27,5	5
CP220VA10HTS	M20x1,5	7,0 - 10,5	8,0 - 10,5	9	33	21	19	24	27,5	5
CP220VA11HTS	M20x1,5	8,0 - 11,0	9,5 - 11,0	9	33	21	19	24	27,5	5
CP220VA12HTS	M20x1,5	10,0 - 12,5	10,0 - 12,0	9	33	21	19	24	27,5	5
CP225VA12HTS	M25x1,5	10,5 - 13,0	11,0 - 13,0	10	34	21,5	24	30	33,4	5
CP225VA13HTS	M25x1,5	11,0 - 13,0	12,0 - 13,0	10	34	21,5	24	30	33,4	5
CP225VA14HTS	M25x1,5	11,0 - 14,0	13,0 - 14,0	10	34	21,5	24	30	33,4	5
CP225VA15HTS	M25x1,5	12,0 - 15,0	14,0 - 15,0	10	34	21,5	24	30	33,4	5
CP225VA16HTS	M25x1,5	13,0 - 16,0	15,0 - 16,0	10	34	21,5	24	30	33,4	5
CP225VA17HTS	M25x1,5	14,0 - 17,0	16,0 - 17,0	10	34	21,5	24	30	33,4	5
CP225VA18HTS	M25x1,5	16,0 - 18,5	17,0 - 18,0	10	34	21,5	24	30	33,4	5
CP232VA18HTS	M32x1,5	15,0 - 18,5	16,0 - 18,5	11	41	26	30	36	40	5
CP232VA19HTS	M32x1,5	16,0 - 19,5	17,0 - 19,5	11	41	26	30	36	40	5
CP232VA20HTS	M32x1,5	16,0 - 20,5	17,5 - 20,5	11	41	26	30	36	40	5
CP232VA21HTS	M32x1,5	18,0 - 21,5	18,5 - 21,5	11	41	26	30	36	40	5
CP232VA22HTS	M32x1,5	18,0 - 22,0	19,0 - 22,0	11	41	26	30	36	40	5
CP232VA23HTS	M32x1,5	19,0 - 23,0	20,0 - 23,0	11	41	26	30	36	40	5