



## Cable Gland PVDF IP68 UNI Dicht PG

\* Material POM (white colour), temperature range -40°C up to +110°C, no CSA approval

### Specification

<b>MATERIAL</b>	PVDF V-0
<b>SEALING RING</b>	TPE
<b>INGRESS PROTECTION</b>	IP68 up to 10 bar
<b>TEMPERATURE RANGE</b>	-40°C...+130°C
<b>COLOUR</b>	Transparent

### Variants

E-NUMBER	ARTICLE NO.	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	SW2 MM	E1 MM	E2 MM	PCS/PACK
N9504000	149Y7	PG7/12,5	4,0 - 6,5	8	31	15	15	16.6	16.6	50
N9505000	14950Y8	PG7/12,5	5,0 - 8,0	8	31	19	19	21.2	21.2	50
N9505001	14950Y9	PG7/12,5	6,5 - 9,5	8	31	19	19	21.2	21.2	50
N9504001	150Y7	PG9/15,2	4,0 - 6,5	8	32	19	19	21.2	21.2	50
N9504002	150Y8	PG9/15,2	5,0 - 8,0	8	32	19	19	21.2	21.2	50
N9504003	150Y9	PG9/15,2	6,5 - 9,5	8	32	19	19	21.2	21.2	50
N9505002	15051Y11	PG9/15,2	7,0 - 10,5	8	31	22	22	24.5	24.5	50
N9505003	15052Y13	PG9/15,2	9,0 - 13,0	8.5	34,5	24	24	26.5	26.5	50
N9504004	151Y7	PG11/18,6	4,0 - 6,5	8	32	22	22	24.4	24.4	50
N9504005	151Y8	PG11/18,6	5,0 - 8,0	8	32	22	22	24.4	24.4	50
N9504006	151Y9	PG11/18,6	6,5 - 9,5	8	32	22	22	24.4	24.4	50

N9504007	151Y11	PG11/18,6	7,0 - 10,5	8	32	22	22	24.4	24.4	50
N9505004	15152Y13	PG11/18,6	9,0 - 13,0	8	34	24	24	26.5	26.5	50
N9505005	15153Y16	PG11/18,6	11,5 - 15,5	9	36	27	27	29.5	29.5	50
N9504008	152Y7	PG13,5/20,4	4,0 - 6,5	9	35	24	24	26.5	26.5	50
N9504009	152Y8	PG13,5/20,4	5,0 - 8,0	9	35	24	24	26.5	26.5	50
N9504010	152Y9	PG13,5/20,4	6,5 - 9,5	9	35	24	24	26.5	26.5	50
N9504011	152Y11	PG13,5/20,4	7,0 - 10,5	9	35	24	24	26.5	26.5	50
N9504012	152Y13	PG13,5/20,4	9,0 - 13,0	9	35	24	24	26.5	26.5	50
N9505006	15253Y16	PG13,5/20,4	11,5 - 15,5	8.5	35,5	27	27	29.5	29.5	50
N9505007	15254Y18	PG13,5/20,4	14,0 - 18,0	9	39	33	33	36.5	36.5	50
N9505008	15254Y20	PG13,5/20,4	17,0 - 20,5	9	39	33	33	36.5	36.5	25
N9504013	153Y7	PG16/22,5	4,0 - 6,5	9	35	27	27	29.5	29.5	50
N9504014	153Y8	PG16/22,5	5,0 - 8,0	9	35	27	27	29.5	29.5	50
N9504015	153Y9	PG16/22,5	6,5 - 9,5	9	35	27	27	29.5	29.5	50
N9504016	153Y11	PG16/22,5	7,0 - 10,5	9	35	27	27	29.5	29.5	50
N9504017	153Y13	PG16/22,5	9,0 - 13,0	9	35	27	27	29.5	29.5	50
N9504018	153Y16	PG16/22,5	11,5 - 15,5	9	35	27	27	29.5	29.5	50
N9505009	15354Y18	PG16/22,5	14,0 - 18,0	9	39	33	33	36.5	36.5	25
N9505010	15354Y20	PG16/22,5	17,0 - 20,5	9	39	33	33	36.5	36.5	25
N9505011	15355Y25	PG16/22,5	20,0 - 25,0	10	42	43	43	46.5	46.5	10
N9505012	15355Y28	PG16/22,5	24,0 - 28,0	10	42	43	43	46.5	46.5	10
N9504019	154Y11	PG21/28,3	7,0 - 10,5	11	40	33	33	36.5	36.5	25
N9504020	154Y13	PG21/28,3	9,0 - 13,0	11	40	33	33	36.5	36.5	25
N9504021	154Y16	PG21/28,3	11,5 - 15,5	11	40	33	33	36.5	36.5	25
N9504022	154Y18	PG21/28,3	14,0 - 18,0	11	40	33	33	36.5	36.5	25
N9504023	154Y20	PG21/28,3	17,0 - 20,5	11	40	33	33	36.5	36.5	25
N9505013	15455Y25	PG21/28,3	20,0 - 25,0	11	44	43	43	46.5	46.5	10
N9505014	15455Y28	PG21/28,3	24,0 - 28,0	11	44	43	43	46.5	46.5	10
N9505015	15456Y32	PG21/28,3	27,0 - 32,0	10	45	53	53	57	57	5
N9505016	15456Y34	PG21/28,3	29,0 - 34,0	10	45	53	53	57	57	5
N9505017	15456Y36	PG21/28,3	32,0 - 36,0	10	45	53	53	57	57	5
-	155Y13	PG29/37,0	9,0 - 13,0	10.5	43,5	43	43	46.5	46.5	10
N9504024	155Y16	PG29/37,0	11,5 - 15,5	10.5	43,5	43	43	46.5	46.5	10
N9504025	155Y18	PG29/37,0	14,0 - 18,0	10.5	43,5	43	43	46.5	46.5	10
N9504026	155Y20	PG29/37,0	17,0 - 20,5	10.5	43,5	43	43	46.5	46.5	10
N9504027	155Y25	PG29/37,0	20,0 - 25,0	10.5	43,5	43	43	46.5	46.5	10
N9504028	155Y28	PG29/37,0	24,0 - 28,0	10.5	43,5	43	43	46.5	46.5	10
N9505018	15556Y32	PG29/37,0	27,0 - 32,0	11	46	53	53	57	57	5
N9505019	15556Y34	PG29/37,0	29,0 - 34,0	11	46	53	53	57	57	5
N9505020	15556Y36	PG29/37,0	32,0 - 36,0	11	46	53	53	57	57	5

N9504029	156Y32	PG36/47,0	27,0 - 32,0	13	47	53	53	57	57	5
N9504030	156Y34	PG36/47,0	29,0 - 34,0	13	47	53	53	57	57	5
N9504031	156Y36	PG36/47,0	32,0 - 36,0	13	47	53	53	57	57	5
-	157Y36*	PG42/54,0	32,0 - 36,0	13	51	60	60	65	65	5
-	157Y40*	PG42/54,0	36,0 - 40,0	13	51	60	60	65	65	5
-	158Y44*	PG48/59,3	39,0 - 44,0	14	55	65	65	70	70	5