



Locknut Polyamide V-0 Metric

- Flame protection acc.to UL 94 V-0

Specification

| | |
|--------------------------|--|
| MATERIAL | Polyamide flame-retardent |
| TEMPERATURE RANGE | -40°C...+100°C |
| COLOUR | Lightgrey RAL7035 |
| FLAME PROTECTION | Glow wire test 960°C at 0,8mm wall thickness |
| HALOGEN-FREE | Yes |

Variants

| ARTICLE NO. | INTERNAL THREAD | H MM | SW1 MM | PCS/PACK |
|-----------------|-----------------|------|--------|----------|
| 50.212PA/FL7035 | M12x1,5 | 5 | 17 | 100 |
| 50.216PA/FL7035 | M16x1,5 | 5 | 22 | 100 |
| 50.220PA/FL7035 | M20x1,5 | 6 | 27 | 100 |
| 50.225PA/FL7035 | M25x1,5 | 6 | 32 | 100 |
| 50.232PA/FL7035 | M32x1,5 | 7 | 41 | 100 |
| 50.240PA/FL7035 | M40x1,5 | 7 | 50 | 50 |
| 50.250PA/FL7035 | M50x1,5 | 8 | 60 | 50 |
| 50.263PA/FL7035 | M63x1,5 | 8 | 75 | 50 |