

Cable Gland Polyamide IP68 RAL 9005 long connection thread Metric

M32x1,5 - M63x1,5 provided with flat sealing ring made of Chloroprene on external thread.

- Long connection thread
- Integrated anchorage
- Easy-to-install

Specification

MATERIAL	Polyamide PA6 V-2
SEALING RING	Polychloroprene-Nitrile rubber CR/NBR
INGRESS PROTECTION	IP68 - 5 bar
TEMPERATURE RANGE	-20°C....+100°C (dynamisk) -40°C (static, short term)
COLOUR	Black RAL 9005
TEST STANDARD	EN 62444 / UL514B
VDE LICENCE	40020902
UL / CSA-FILE	E140310
SEV LICENCE	01.1135
HALOGEN-FREE	Yes

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

E-NUMBER	CONNECTION THREAD	FOR CABLE Ø MM	L MM	H MM	SW1 MM	E1 MM	PCS/PACK
1475911	M12x1,5	3 - 6	15	38	15	16.5	100
1475912	M16x1,5	5 - 9,5	15	42,5	20	22	100
1475913	M20x1,5	8 - 13	15	43	24	26.5	100
1475914	M25x1,5	11 - 17	15	50	29	32	50
1475915	M32x1,5	15 - 21	15	55	36	40	25
1475916	M40x1,5	19 - 28	18	59	46	51	10
1475917	M50x1,5	27 - 35	18	67,5	55	60	5
1475918	M63x1,5	32 - 42	18	71,5	68	75	5

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö