



TKS - KLIKSEAL® RAL 9005

Material thickness 2 - 5 mm

- Integrated cable anchorage
- Handles large range of cable and pipe diameter
- Quick and simple assembly without the use of tools
- Ergonomic installation

(1) Unstressed material.

* Cable Anchorage Type A, according to EN 50262.
** 8,1 - 8,9 mm only approved for tension relief.
*** Varies depending on the thickness of material installed in.

Specification

MATERIAL	TPE and Polyamide 66 UL listed material
INGRESS PROTECTION	IP65
TEMPERATURE RANGE	-20°C....+125°C (1)
COLOUR	Black RAL 9005
TEST STANDARD	EN60529:1991 + A1, EN50262:1998 + A1 + A2
SEMKO REPORT	SE-S-2400409
HALOGEN-FREE	Yes

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

E-NUMBER	SIZE	IP65 AND CABLE ANCHORAGE TYPE A* FOR CABLE Ø MM	A MM	B MM	D*** MM	D1 MM	H MM	H2 MM	PCS/PACK
1475811	M20	7 - 11	20.5	2 - 5	29,3 - 34,5	4	17 - 20	5.5	50
1475812	M25	7 - 13**	25.5	2 - 5	34,3 - 40,0	5	17 - 20	5.5	50

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö