



TKS - KLIKSEAL® for thin materials RAL 9005

Material thickness M20 0,5 - 3 mm, M25 0,9 - 3 mm

- Integrated cable anchorage
- Handles large range of cable and pipe diameter
- Quick and simple assembly without the use of tools
- Ergonomic installation

(1) Unstressed material.

* Cable Anchorage Type A, according to EN 50262.

** 8,1 - 8,9 mm only approved for tension relief.

*** Varies depending on the thickness of material installed in.

Specification

MATERIAL	TPE and Polyamide 66 UL listed material
INGRESS PROTECTION	IP65
TEMPERATURE RANGE	-20°C.....+125°C (1)
COLOUR	Black RAL 9005
TEST STANDARD	EN 60529:1991+A1, EN 50262:1998
SEMKO REPORT	2002136
HALOGEN-FREE	Yes

Variants

E-NUMBER	SIZE	IP65 AND CABLE ANCHORAGE TYPE A* FOR CABLE Ø MM	A MM	B MM	D*** MM	D1 MM	H MM	H2 MM	PCS/PACK
1475832	M20	7 - 11	20.5	0,5 - 3	34,2 - 37,2	4	17 - 20	5.5	50
1475833	M25	7 - 13**	25.5	0,9 - 3	39,2 - 42,2	5	17 - 20	5.5	50