



TRS - RUTASEAL® EPDM Metric RAL7035

Suitable for holes in materials of 0,5 - 4mm thickness.

- Quick and simple assembly without the use of tools
- Resistant to chemicals
- Weatherproof

(1) Unstressed material.

Specification

MATERIAL	EPDM
INGRESS PROTECTION	IP67 acc. to EN 60529
TEMPERATURE RANGE	-40°C....+110°C (1)
COLOUR	Lightgrey RAL 7035
TEST STANDARD	EN IEC 60670-1:2021+A11 EN 60670-1:2005+A1:2013
SEMKO REPORT	2300448 2002163 (M63) 2100897 (M12F, M16F)
HALOGEN-FREE	Yes

Variants

E-NUMBER	SIZE	FOR CABLE Ø MM	A MM	B MM	D MM	H MM	H1 MM	PCS/PACK
1458303	M12	4 - 7	12.5	0,5-2	20	12,7	5.4	50
TRS EPDM M12 7035 F	M12	4 - 7	12.5	2-5	20	12,7	5.4	50
1458304	M16	5 - 9	16.5	1-4	21	18	10.5	50
TRS EPDM M16 7035 F	M16	5 - 9	16.5	2-5	21	18	10.5	50
1458305	M20	8 - 13	20.5	1-4	25,5	20	12.7	50
1458306	M25	11 - 17	25.5	1-4	30,5	21,6	14.5	50
1458307	M32	15 - 20	32.5	1-4	38,5	24,8	17.5	25
1458308	M40	19 - 28	40.5	1-4	48,5	30	20.4	25
1458309	M50	27- 35	50.5	1-4	60,5	35	23.9	10
1458337	M63	34 - 45	63.5	1-4	73,5	40	28.9	5