



## TRS - RUTASEAL® EPDM Metric RAL9005

Suitable for holes in materials of 0,5 - 4mm thickness.

- Quick and simple assembly without the use of tools
- Resistant to chemicals
- Weatherproof

### Specification

#### INFORMATION\_KLIKSEAL

(1) Unstressed material.

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| <b>MATERIAL</b>           | EPDM                                               |
| <b>INGRESS PROTECTION</b> | IP67 acc. to EN 60529                              |
| <b>TEMPERATURE RANGE</b>  | -40°C....+110°C (1)                                |
| <b>COLOUR</b>             | Black RAL 9005                                     |
| <b>TEST STANDARD</b>      | EN IEC 60670-1:2021+A11<br>EN 60670-1:2005+A1:2013 |
| <b>SEMKO REPORT</b>       | 2300448<br>2002163 (M63)<br>2100897 (M12F, M16F)   |
| <b>HALOGEN-FREE</b>       | Yes                                                |

## Variants

| E-NUMBER            | SIZE | FOR CABLE Ø MM | A MM | B MM  | D MM | H MM | H1 MM | PCS/PACK |
|---------------------|------|----------------|------|-------|------|------|-------|----------|
| 1458293             | M12  | 4 - 7          | 12.5 | 0,5-2 | 20   | 12,7 | 5.4   | 50       |
| TRS EPDM M12 9005 F | M12  | 4 - 7          | 12.5 | 2-5   | 20   | 12,7 | 5.4   | 50       |
| 1458294             | M16  | 5 - 9          | 16.5 | 1-4   | 21   | 18   | 10.5  | 50       |
| TRS EPDM M16 9005 F | M16  | 5 - 9          | 16.5 | 2-5   | 21   | 18   | 10.5  | 50       |
| 1458295             | M20  | 8 - 13         | 20.5 | 1-4   | 25,5 | 20   | 12.7  | 50       |
| 1458296             | M25  | 11 - 17        | 25.5 | 1-4   | 30,5 | 21,6 | 14.5  | 50       |
| 1458297             | M32  | 15 - 20        | 32.5 | 1-4   | 38,5 | 24,8 | 17.5  | 25       |
| 1458298             | M40  | 19 - 28        | 40.5 | 1-4   | 48,5 | 30   | 20.4  | 25       |
| 1458299             | M50  | 27 - 35        | 50.5 | 1-4   | 60,5 | 35   | 23.9  | 10       |
| 1458300             | M63  | 34 - 45        | 63.5 | 1-4   | 73,5 | 40   | 28.9  | 5        |