



TRS - RUTASEAL® EPDM PG RAL7035

Suitable for holes in materials of 0,5 - 4mm thickness.

- Quick and simple assembly without the use of tools
- Resistant to chemicals
- Weatherproof

Specification

INFORMATION_KLIKSEAL

(1) Unstressed material.

MATERIAL	EPDM
INGRESS PROTECTION	IP67 acc. to EN 60529
TEMPERATURE RANGE	-40°C....+110°C (1)
COLOUR	Lightgrey RAL 7035
TEST STANDARD	EN60670-1:2005+A1:2013
SEMKO REPORT	2002133
HALOGEN-FREE	Yes

Variants

E-NUMBER	SIZE	FOR CABLE Ø MM	A MM	B MM	D MM	H MM	H1 MM	PCS/PACK
1458212	PG7/12,5	3 - 5	13	0,5-2	20	12,7	5.4	50
1458213	PG9/15,2	5 - 7	16	1-4	21	18	10.3	50
1458214	PG11/18,6	7 - 10	19	1-4	24	20	12.7	50
1458215	PG16/22,5	10 - 14	23	1-4	28	21,6	14.7	50
1458216	PG21/28,3	14 - 20	29	1-4	35	24,8	17.6	25
1458217	PG29/37,0	20 - 26	38	1-4	46	28,5	20	25
1458218	PG36/47,0	26 - 35	48	1-4	58	35	23.9	10