



## TSS RAL9005 Metric

Suitable for holes in material of 0,5 - 4,5 mm thickness.

- Quick and simple assembly without the use of tools
- Handles exceptionally large cable span
- An end-plug for all applications

(1) Unstressed material.

\* Varies depending on the thickness of material installed in.

## Specification

|                           |  |
|---------------------------|--|
| <b>MATERIAL</b>           | TPE - Thermoplastic Elastomer - UL listed material |
| <b>INGRESS PROTECTION</b> | IP67   |
| <b>TEMPERATURE RANGE</b>  | -50°C...+125°C (1)                                 |
| <b>COLOUR</b>             | Black RAL 9005                                     |
| <b>TEST STANDARD</b>      | EN60670-1:2005+A1:2013                             |
| <b>SEMKO REPORT</b>       | SE-S-2100893                                       |
| <b>HALOGEN-FREE</b>       | Yes  |

## Variants

| E-NUMBER | SIZE | FOR CABLE Ø MM | A MM | B MM      | D* MM | D1 MM | H MM | H1 MM | H2* MM | PCS/PACK | BVB   |
|----------|------|----------------|------|-----------|-------|-------|------|-------|--------|----------|---|
| 1475716  | M16  | 5 - 10         | 16.5 | 0,5 - 3   | 23.5  | 4     | 11   | 4     | 6.75   | 50       |  |
| 1475717  | M20  | 6 - 13         | 20.5 | 0,5 - 3   | 27.5  | 5     | 11   | 4     | 6.75   | 50       |  |
| 1475718  | M25  | 8 - 17         | 25.5 | 0,5 - 3,5 | 32.5  | 7     | 11   | 4     | 6.75   | 50       |  |
| 1475719  | M32  | 12 - 24        | 32.5 | 0,5 - 4,5 | 39.5  | 11    | 11   | 4     | 6.75   | 25       |  |
| 1475720  | M40  | 19 - 31        | 40.5 | 1,5 - 4,5 | 47.5  | 18    | 13.5 | 4.84  | 7.41   | 25       |  |