



Novotronic Profinet® UL/CSA Typ B FRNC

Halogen free industrial 100Mbit/s Ethernet cable

Specification

| | |
|----------------------------------|--|
| RATED VOLTAGE ACC TO. UL/CSA | 300V |
| RATED VOLTAGE UO/U CONTROL CORES | 125V |
| CONDUCTOR CLASS | 7-wire (AWG22/7) |
| CONDUCTOR MATERIAL | Tinned Copper |
| CORE INSULATION | PE |
| CORE IDENTIFICATION | White, Yellow, Blue and Orange |
| OVERALL SHIELD | Aluminum foil and braided tinned copper wire |
| OUTER SHEATH | Halogen free mix |
| BENDING RADIUS FIXED | 5 x cable diameter |
| BENDING RADIUS MOVED | 10 x cable diameter |
| MIN OPERATING TEMPERATURE FIXED | -20°C |
| MAX OPERATING TEMPERATURE FIXED | +75°C |
| MIN OPERATING TEMPERATURE MOVED | -10°C |
| MAX OPERATING TEMPERATURE MOVED | +50°C |
| INSULATION RESISTANCE | Min. 5 G Ohm x km |
| IMPEDANCE | 100 Ohm |
| HALOGEN-FREE ACC. TO | IEC 60754 |
| FLAME RETARDANT | IEC 60332-1 |

Variants

| NO OF CORES X AWG | OUTER DIAMETER MM | WEIGHT KG/100M | BVB |
|-------------------|-------------------|----------------|---|
| 2x2xAWG22/7 | 6.5 | 6.5 |  |