



RKK (H05VV-F)

PVC-sheathed installation cable

Specification

STANDARD	HD 21.5
APPROVALS	Cenelec HAR
RATED VOLTAGE U ₀ /U	300/500V
CONDUCTOR CLASS	Class 5 = fine stranded wires
CONDUCTOR MATERIAL	Copper
CORE INSULATION	PVC
CORE IDENTIFICATION	Colour coded
PROTECTIVE CONDUCTOR	Yellow/Green
OUTER SHEATH	PVC
BENDING RADIUS FIXED	6 x cable diameter
BENDING RADIUS MOVED	6 x cable diameter
MIN OPERATING TEMPERATURE FIXED	-40°C
MAX OPERATING TEMPERATURE FIXED	+70°C
MIN OPERATING TEMPERATURE MOVED	+5°C
MAX OPERATING TEMPERATURE MOVED	+70°C
TESTING VOLTAGE	2000V
FLAME RETARDANT	IEC 60332-1

Variants

E-NUMBER	DIMENSION N X MM ²	OUTER DIAMETER MM	WEIGHT KG/100M	COLOUR	LENGTH	PACKAGING TYPE
0508362	2x0,75	6.3	5.2	White	100 meters	Ring
0508452	3G0,75	6.8	7	White	100 meters	Ring
N9270530	3G0,75	6.8	7	Grey	100 meters	Ring
0508602	5G0,75	8.3	9.6	White	100 meters	Ring
0508492	3G1,0	7	8	White	100 meters	Ring
0508412	2x1,5	7.6	9	White	100 meters	Ring
0508512	3G1,5	8.1	11.5	White	100 meters	Ring
0508582	4G1,5	9.2	14.5	White	100 meters	Ring
0508622	5G1,5	10.5	17.5	White	100 meters	Ring
0508661	5G2,5	12.5	26	White	50 meters	Ring