



DeviceNet PMXX-ST

Highly flexible PUR sheathed Trunk & Drop cable for DeviceNet

Specification

RATED VOLTAGE UO/U CONTROL CORES	300V
CONDUCTOR CLASS	19-wire
CONDUCTOR MATERIAL	Tinned Copper
CORE INSULATION	Supply cores: Polyolefin, Control cores: PE
CORE IDENTIFICATION	Supply pair: Black, red. Data pair: Blue, white
PAIR SCREEN	Aluminium foil
OVERALL SHIELD	Aluminum foil+tinned drain wire and braided tinned copper wire
OUTER SHEATH	PUR
SHEAT COLOUR	Violet RAL 4001
MIN OPERATING TEMPERATURE FIXED	-40°C
MAX OPERATING TEMPERATURE FIXED	+80°C
MIN OPERATING TEMPERATURE MOVED	-30°C
MAX OPERATING TEMPERATURE MOVED	+70°C
TESTING VOLTAGE	1500V
FLAME RETARDANT	IEC 60332-1

Variants

E-NUMBER	NO OF CORES X AWG	OUTER DIAMETER MM	WEIGHT KG/100M
N7780740	1x2x18+1x2x15	12.2	20.3
N7780750	1x2x24+1x2x22	7	6.8

