



## FLAQQBR

Halogen free combined power and signalling cable

### Specification

<b>RATED VOLTAGE U<sub>0</sub>/U</b>	100V
<b>CONDUCTOR CLASS</b>	Class 2 = stranded wires
<b>CONDUCTOR MATERIAL</b>	Copper
<b>CORE INSULATION</b>	Halogen free compund
<b>CORE IDENTIFICATION</b>	Colour coded
<b>FABRIC LAPPING</b>	Foil
<b>SHIELD CONTROL PAIRS</b>	Aluminiumfoil with tinned copper drain wire
<b>OUTER SHEATH</b>	Halogen free mix
<b>SHEAT COLOUR</b>	White
<b>MIN OPERATING TEMPERATURE FIXED</b>	-15°C
<b>MAX OPERATING TEMPERATURE FIXED</b>	+80°C
<b>LOWEST INSTALLATION TEMPERATURE</b>	-10°C
<b>CONDUCTOR RESISTANCE</b>	0,22mm <sup>2</sup> max 90 Ohm/km, 1,0mm <sup>2</sup> max 20,2 Ohm/km
<b>CAPACITANCE</b>	max. 75 nF/km
<b>BURNING BEHAVIOR CPR</b>	Dca-s2,d2,a1
<b>FLAME RETARDANT</b>	IEC 60332-1

## Variants

DIMENSION N X MM <sup>2</sup>	OUTER DIAMETER MM	WEIGHT KG/100M	LENGTH	PACKAGING TYPE	BVB
2x1+1x2x0,22	6.5	5.1	500 meters	Bobin	
4x1+2x2x0,22	8.7	6.2	500 meters	Bobin	