



Spiral cable H05BQ-F, H07BQ-F

Rubber insulated PUR-sheathed spiral cable

Specification

APPROVALS	Cenelec HAR
RATED VOLTAGE UO/U	450/750V
CONDUCTOR CLASS	Class 6 = extra fine stranded wires
CONDUCTOR MATERIAL	Copper
CORE INSULATION	Rubber (7 cores = TPE)
CORE IDENTIFICATION	≤5 cores: Colour coded, ≥7 cores: Black with numerals
PROTECTIVE CONDUCTOR	Yellow/Green
OUTER SHEATH	PUR
MIN OPERATING TEMPERATURE MOVED	-30°C
MAX OPERATING TEMPERATURE MOVED	+60°C
TESTING VOLTAGE	2000-3000V
FLAME RETARDANT	IEC 60332-1

Variants

E-NUMBER	DIMENSION N X MM ²	RETRACTED SPIRAL LENGTH MM	EXTENDED SPIRAL LENGTH MM	LENGTH OF END MM	OUTER DIAM COILED CABLE MM	COLOUR
N8205150	2x1,0	500	2000	500	25.2	Black
N8205151	2x1,0	1000	4000	500	25.2	Black
N8205152	2x1,0	1500	6000	500	25.2	Black
N8205153	2x1,0	1500	6000	2500	25.2	Black

2404139	3G1,0	500	2000	500	27.2	Black
2404140	3G1,0	1000	4000	500	27.2	Black
2404141	3G1,0	1500	6000	500	27.2	Black
N8205163	3G1,0	1500	6000	2500	27.2	Black
N8205170	4G1,0	500	2000	500	29.4	Black
N8205171	4G1,0	1000	4000	500	29.4	Black
N8205172	4G1,0	1500	6000	500	29.4	Black
N8205173	4G1,0	1500	6000	2500	29.4	Black
N8205180	5G1,0	500	2000	500	34	Black
N8205181	5G1,0	1000	4000	500	34	Black
N8205182	5G1,0	1500	6000	500	34	Black
N8205183	5G1,0	1500	6000	2500	34	Black
N8205190	7G1,0	500	2000	500	39.8	Black
N8205191	7G1,0	1000	4000	500	39.8	Black
N8205192	7G1,0	1500	6000	500	39.8	Black
N8205193	7G1,0	1500	6000	2500	39.8	Black
N8205200	2x1,5	500	2000	500	31.8	Black
N8205201	2x1,5	1000	4000	500	31.8	Black
N8205202	2x1,5	1500	6000	500	31.8	Black
N8205203	2x1,5	1500	6000	2500	31.8	Black
2404142	3G1,5	500	2000	500	32.6	Black
2404143	3G1,5	1000	4000	500	32.6	Black
2404144	3G1,5	1500	6000	500	32.6	Black
N8205213	3G1,5	1500	6000	2500	32.6	Black
2404145	4G1,5	500	2000	500	37.4	Black
2404146	4G1,5	1000	4000	500	37.4	Black
2404147	4G1,5	1500	6000	500	37.4	Black
N8205223	4G1,5	1500	6000	2500	37.4	Black
2404148	5G1,5	500	2000	500	39.2	Black
2404149	5G1,5	1000	4000	500	39.2	Black
2404150	5G1,5	1500	6000	500	39.2	Black
N8205233	5G1,5	1500	6000	2500	39.2	Black
N8205240	3G2,5	500	2000	500	38.8	Orange
N8205241	3G2,5	1000	4000	2000	38.8	Orange
N8205250	4G2,5	500	2000	500	43.2	Orange
N8205251	4G2,5	1000	4000	2000	43.2	Orange
N8205260	5G2,5	500	2000	500	49	Orange

N8205261	5G2,5	1000	4000	2000	49	Orange
----------	-------	------	------	------	----	--------