



Surface mounting socket outlet

Low-voltage

Specification

MATERIAL	Polyamide
MATERIAL TERMINALS	Brass
INGRESS PROTECTION	IP44

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	RATED CURRENT (A)	NUMBER OF POLES	VOLTAGE / COLOR CODE	CABLE ENTRIES MM	PCS/PACK
2421664	460	Surface mounting socket outlet, 2-pol, 16A, 24V	16	2	24V / Violet	M25	10
2421665	466	Surface mounting socket outlet, 3-pol, 16A, 24V	16	3	24V / Violet	M25	10
-	4611	Surface mounting socket outlet, 2-pol, 32A, 24V	32	2	24V / Violet	M25	10
-	4617	Surface mounting socket outlet, 3-pol, 32A, 24V	32	3	24V / Violet	M25	10
-	461	Surface mounting socket outlet, 2-pol, 16A, 42V	16	2	42V / Grey	M25	10
-	467	Surface mounting socket outlet, 3-pol, 16A, 42V	16	3	42V / Grey	M25	10

-	4612	Surface mounting socket outlet, 2-pol, 32A, 42V	32	2	42V / Grey	M25	10
-	4618	Surface mounting socket outlet, 3-pol, 32A, 42V	32	3	42V / Grey	M25	10
-	462	Surface mounting socket outlet, 2-pol, 16A, ≤50V, 100-200Hz	16	2	≤50 V, 100-200Hz / Green	M25	10
-	468	Surface mounting socket outlet, 3-pol, 16A, ≤50V, 100-200Hz	16	3	≤50 V, 100-200Hz / Green	M25	10
-	4613	Surface mounting socket outlet, 2-pol, 32A, ≤50V, 100-200Hz	32	2	≤50 V, 100-200Hz / Green	M25	10
-	4619	Surface mounting socket outlet, 3-pol, 32A, ≤50V, 100-200Hz	32	3	≤50 V, 100-200Hz / Green	M25	10
-	463	Surface mounting socket outlet, 2-pol, 16A, ≤50V, 300Hz	16	2	>50 V, 300Hz / Green	M25	10
-	469	Surface mounting socket outlet, 3-pol, 16A, ≤50V, 300Hz	16	3	>50 V, 300Hz / Green	M25	10
-	4614	Surface mounting socket outlet, 2-pol, 32A, ≤50V, 300Hz	32	2	>50 V, 300Hz / Green	M25	10
-	4620	Surface mounting socket outlet, 3-pol, 32A, ≤50V, 300Hz	32	3	>50 V, 300Hz / Green	M25	10
-	464	Surface mounting socket outlet, 2-pol, 16A, ≤50V, 40000Hz	16	2	≤50 V, 400Hz / Green	M25	10
-	4610	Surface mounting socket outlet, 3-pol, 16A, ≤50V, 400Hz	16	3	≤50 V, 400Hz / Green	M25	10
-	4615	Surface mounting socket outlet, 2-pol, 32A, ≤50V, 400Hz	32	2	≤50 V, 400Hz / Green	M25	10
-	4621	Surface mounting socket outlet, 3-pol, 32A, ≤50V, 400Hz	32	3	≤50 V, 400Hz / Green	M25	10