



Connector MIL IP67

63A / 125A

- Connecot with screw terminals and Multi-Grip
- IP67/IP69
- Simultaneous cable gland and seal
- With pilot contact

Specification

MATERIAL ENCLOSURE	Polyamide
MATERIAL TERMINALS	Brass nickel plated
CONNECTION CAPACITY	63A: 6 - 16mm ² 125A: 16 - 50mm ²
INGRESS PROTECTION	IP67 / IP69
STANDARDS	IEC 60309, EN 60309, VDE 0623, VG 96926 *according to VG 96919
COLOUR	RAL 6031-F9 - Bronze-green

Variants

ARTICLE NO.	DESCRIPTION	RATED CURRENT (A)	NUMBER OF POLES	VOLTAGE / COLOR CODE	CABLE ENTRIES MM	PCS/PACK
310058	263-6 (DS 047)	63	3	230V / Blue	16 - 36	5
310174	363-9 (DS 030)	63	4	230V / Blue	16 - 36	5
31324*	463-9 (DS 010)	63	5	230V / Blue	16 - 36	5
310059	2125-6 (DS 052)	125	3	230V / Blue	26 - 50	5
310180	3125-9 (DS 035)	125	4	230V / Blue	26 - 50	5
31327*	4125-9 (DS 014)	125	5	230V / Blue	26 - 50	5
31877	363-6 (DS 028)	63	4	400V / Red	16 - 36	5
31152*	463-6 (DS 009)	63	5	400V / Red	16 - 36	5
310060	3125-6 (DS 033)	125	4	400V / Red	26 - 50	5
31027*	4125-6 (DS 013)	125	5	400V / Red	26 - 50	5