



Panel Mounted Socket Outlet Angled MIL IP67

63A / 125A

- Panel Mounting Appliance Outlet with Screw Terminals
- Angled 15°
- IP67/IP69
- With pilot contact
- Flange: 114x114mm

Specification

MATERIAL ENCLOSURE	Polyamide
MATERIAL TERMINALS	Brass nickel plated
CONNECTION CAPACITY	63A max. 25mm ² 125A max. 70mm ²
INGRESS PROTECTION	IP67 / IP69
STANDARDS	IEC 60309, EN 60309, VDE 0623, VG 96926 *according to VG 96919
COLOUR	RAL 6031-F9 - Bronze-green

Variants

ARTICLE NO.	DESCRIPTION	RATED CURRENT (A)	NUMBER OF POLES	VOLTAGE / COLOR CODE	FIXING HOLES MM	PCS/PACK
12239	263-6 (BS 047)	63	3	230V / Blue	90 x 90	5
120035	363-9 (BS 030)	63	4	230V / Blue	90 x 90	5
12341*	463-9 (BS 010)	63	5	230V / Blue	90 x 90	5
12954	2125-6 (BS 052)	125	3	230V / Blue	90 x 90	5
120041	3125-9 (BS 035)	125	4	230V / Blue	90 x 90	5
12342*	4125-9 (BS 014)	125	5	230V / Blue	90 x 90	5
12953	363-6 (BS 028)	63	4	400V / Red	90 x 90	5
12088*	463-6 (BS 009)	63	5	400V / Red	90 x 90	5
12955	3125-6 (BS 033)	125	4	400V / Red	90 x 90	5
12191*	4125-6 (BS 013)	125	5	400V / Red	90 x 90	5