



Panel Mounted Socket Outlet Angled QC MIL IP67

16A / 32A

- Panel Mounting Appliance Outlet with Quick-Connect terminals
- Angled 20°
- IP67/IP69
- Flange: 85x85mm

Specification

MATERIAL ENCLOSURE	Polyamide
MATERIAL TERMINALS	Brass nickel plated
CONNECTION CAPACITY	16A max. 4mm ² 32A max. 10mm ²
INGRESS PROTECTION	IP67 / IP69
STANDARDS	IEC 60309, EN 60309, VDE 0623, VG 96926 *according to VG 96919
COLOUR	RAL 6031-F9 - Bronze-green

Variants

ARTICLE NO.	DESCRIPTION	RATED CURRENT (A)	NUMBER OF POLES	VOLTAGE / COLOR CODE	FIXING HOLES MM	PCS/PACK
12085*	216-6 (BS 017)	16	3	230V / Blue	70 x 70	10
120025	316-9 (BS 020)	16	4	230V / Blue	70 x 70	10
12242*	416-9 (BS 002)	16	5	230V / Blue	70 x 70	10
12169	232-6 (BS 042)	32	3	230V / Blue	70 x 70	10
120030	332-9 (BS 025)	32	4	230V / Blue	70 x 70	10
12340*	432-9 (BS 006)	32	5	230V / Blue	70 x 70	10
12699	316-6 (BS 018)	16	4	400V / Red	70 x 70	10
12086*	416-6 (BS 001)	16	5	400V / Red	70 x 70	10
12700	332-6 (BS 023)	32	4	400V / Red	70 x 70	10
12087*	432-6 (BS 005)	32	5	400V / Red	70 x 70	10