



Plug MIL IP67

63A / 125A

- Plug with screw terminals and Multi-Grip
- IP67/IP69
- With protective cap
- Simultaneous cable gland and seal

Specification

MATERIAL ENCLOSURE	Polyamide
MATERIAL TERMINALS	Brass nickel plated
CONNECTION CAPACITY	63A: 6 - 16mm ² 125A: 16 - 50mm ²
INGRESS PROTECTION	IP67 / IP69
STANDARDS	IEC 60309, EN 60309, VDE 0623, VG 96926 *according to VG 96919
COLOUR	RAL 6031-F9 - Bronze-green

Variants

ARTICLE NO.	DESCRIPTION	RATED CURRENT (A)	NUMBER OF POLES	VOLTAGE / COLOR CODE	CABLE ENTRIES MM	PCS/PACK
210256	263-6 (CP 047)	63	3	230V / Blue	16 - 36	5
210414	363-9 (CP 000)	63	4	230V / Blue	16 - 36	5
21428*	463-9 (CP 010)	63	5	230V / Blue	16 - 36	5
210264	2125-6 (CP 052)	125	3	230V / Blue	26 - 50	5
210421	3125-9 (CP 035)	125	4	230V / Blue	26 - 50	5
21431*	4125-9 (CP 014)	125	5	230V / Blue	26 - 50	5
210263	363-6 (CP 028)	63	4	400V / Red	16 - 36	5
21210*	463-6 (CP 009)	63	5	400V / Red	16 - 36	5
210265	3125-6 (CP 033)	125	4	400V / Red	26 - 50	5
21033*	4125-6 (CP 013)	125	5	400V / Red	26 - 50	5