



Plug QC MIL IP67

16A / 32A

- Plug with Quick-Connect and Multi-Grip
- IP67/IP69
- With protective cap
- Simultaneous cable gland and seal

Specification

MATERIAL ENCLOSURE	Polyamide
MATERIAL TERMINALS	Brass nickel plated
CONNECTION CAPACITY	16A max. 2,5mm ² 32A max. 6mm ²
INGRESS PROTECTION	IP67 / IP69
STANDARDS	IEC 60309, EN 60309, VDE 0623, VG 96926 *according to VG 96919
COLOUR	RAL 6031-F9 - Bronze-green

Variants

ARTICLE NO.	DESCRIPTION	RATED CURRENT (A)	NUMBER OF POLES	VOLTAGE / COLOR CODE	CABLE ENTRIES MM	PCS/PACK
21220*	216-6 (CP 017)	16	3	230V / Blue	8 - 18	10
210404	316-9 (CP 020)	16	4	230V / Blue	8 - 18	10
21423*	416-9 (CP 002)	16	5	230V / Blue	10 - 21	10
21221	232-6 (CP 042)	32	3	230V / Blue	11 - 23,5	10
210409	332-9 (CP 025)	32	4	230V / Blue	11 - 23,5	10
21426*	432-9 (CP 006)	32	5	230V / Blue	13 - 27	10
210077	316-6 (CP 018)	16	4	400V / Red	8 - 18	10
21208*	416-6 (CP 001)	16	5	400V / Red	10 - 21	10
210078	332-6 (CP 023)	32	4	400V / Red	11 - 23,5	10
21209*	432-6 (CP 005)	32	5	400V / Red	13 - 27	10