



Straight Appliance inlet MIL IP67

16A / 32A / 63A / 125A

- Appliance Inlet with screw terminals
- IP67/IP69
- With protective cap
- Flange:
16A & 32A: 85x85mm
63A: 110x106mm
125A: 120x120mm

Specification

MATERIAL ENCLOSURE	Polyamide
MATERIAL TERMINALS	Brass nickel plated
CONNECTION CAPACITY	16A max 2,5mm ² 32A max 6mm ² 63A max 16mm ² 125A max 50mm ²
INGRESS PROTECTION	IP67 / IP69
STANDARDS	IEC 60309, EN 60309, VDE 0623, VG 96926 *according to VG 96919
COLOUR	RAL 6031-F9 - Bronze-green

Variants

ARTICLE NO.	DESCRIPTION	RATED CURRENT (A)	NUMBER OF POLES	VOLTAGE / COLOR CODE	FIXING HOLES MM	PCS/PACK
2892	216-6 (AP 037)	16	3	230V / Blue	70 x 70	10
2895	232-6 (AP 042)	32	3	230V / Blue	70 x 70	10
28042	263-6 (AP 047)	63	3	230V / Blue	90 x 90	5
28043	2125-6 (AP 052)	125	3	230V / Blue	100 x 100	5
2893	316-6 (AP 017)	16	4	400V / Red	70 x 70	10
2894	416-6 (AP 001)	16	5	400V / Red	70 x 70	10
2896	332-6 (AP 022)	32	4	400V / Red	70 x 70	10
2897	432-6 (AP 005)	32	5	400V / Red	70 x 70	10
28000	363-6 (AP 027)	63	4	400V / Red	90 x 90	5
2853	463-6 (AP 009)	63	5	400V / Red	90 x 90	5
28044	3125-6 (AP 032)	125	4	400V / Red	100 x 100	5
28045	4125-6 (AP 013)	125	5	400V / Red	100 x 100	5