



Straight Panel Mounting Socket Outlet QC MIL IP67

16A / 32A

- Panel Mounting Appliance Outlet with Quick-Connect terminals
- IP67/IP69
- Flange: 75x75mm

Specification

MATERIAL ENCLOSURE	Polyamide
MATERIAL TERMINALS	Brass nickel plated
CONNECTION CAPACITY	16A max. 4mm ² 32A max. 10mm ²
INGRESS PROTECTION	IP67 / IP69
STANDARDS	IEC 60309, EN 60309, VDE 0623, VG 96926 *according to VG 96919
COLOUR	RAL 6031-F9 - Bronze-green

Variants

ARTICLE NO.	DESCRIPTION	RATED CURRENT (A)	NUMBER OF POLES	VOLTAGE / COLOR CODE	FIXING HOLES MM	PCS/PACK
13064	216-6 (AS 013)	16	3	230V / Blue	60 x 60	10
13928	316-9 (AS 020)	16	4	230V / Blue	60 x 60	10
13189*	416-9 (AS 001)	16	5	230V / Blue	60 x 60	10
13032	232-6 (AS 042)	32	3	230V / Blue	60 x 60	10
13933	332-9 (AS 025)	32	4	230V / Blue	60 x 60	10
13297*	432-9 (AS 006)	32	5	230V / Blue	60 x 60	10
13633	316-6 (AS 018)	16	4	400V / Red	60 x 60	10
13065*	416-6 (AS 001)	16	5	400V / Red	60 x 60	10
13634	332-6 (AS 023)	32	4	400V / Red	60 x 60	10
13066*	432-6 (AS 005)	32	5	400V / Red	60 x 60	10