



Curved elbow conduit-connector 90° with metal thread IP68 Metric

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Nickel-plated brass thread
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation
- High conduit pull-out strength.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide 6 (PA6)
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-40°C....+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	G MM	Ø D MM	A MM	B MM	Ø C MM	R MM	Ø ID MM	PCS/PACK
NVBV-M207-10	M20x1,5	17	10	29	51	73	29.5	30.5	11	50
NVBV-M207-6	M20x1,5	17	6	29	47	73	29.5	30.5	11	50
NVBV-M257-11	M25x1,5	17	11	35	52	76	29.5	30.5	14.5	50
NVBV-M257-7	M25x1,5	17	7	35	48	76	29.5	30.5	14.5	50
NVBV-M253-11	M25x1,5	23	11	35	62.5	85	37	38	15.5	30
NVBV-M253-7	M25x1,5	23	7	35	58.5	85	37	38	15.5	30
NVBV-M323-13	M32x1,5	23	13	43	64.5	89	37	38	19.5	30
NVBV-M323-8	M32x1,5	23	8	43	59.5	89	37	38	19.5	30
NVBV-M329-13	M32x1,5	29	13	43	74	94.5	44	45	23	20
NVBV-M329-8	M32x1,5	29	8	43	69	94.5	44	45	23	20
NVBV-M409-13	M40x1,5	29	13	55	75.5	100.5	44	45	28.5	20
NVBV-M409-8	M40x1,5	29	8	55	70.5	100.5	44	45	28.5	20
NVBV-M406-13	M40x1,5	36	13	55	86.5	123	53.5	53	29	20
NVBV-M406-8	M40x1,5	36	8	55	81.5	123	53.5	53	29	20
NVBV-M506-14	M50x1,5	36	14	69	87.5	130	53.5	53	36.5	20
NVBV-M508-14	M50x1,5	48	14	69	100.5	135	66	60	38.5	10
NVBV-M508-9	M50x1,5	48	9	69	95.5	135	66	60	38.5	10
NVBV-M638-14	M63x1,5	48	14	75	100.5	138	66	60	48	10
NVBV-M638-10	M63x1,5	48	10	75	96.5	138	66	60	48	10

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö