



Elbow conduit-connector 90° with metal thread IP68 Metric

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Nickel-plated brass thread
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation
- High conduit pull-out strength.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide 6 (PA6)
INGRESS PROTECTION	IP68
TEMPERATURE RANGE	-40°C....+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

ARTICLE NO.	CONNECTION THREAD	CONDUIT SIZE	G MM	A MM	B MM	Ø ID MM	Ø D MAX MM	PCS/PACK
NVWV-M120-10	M12x1,5	10	10	37.5	39.5	5	20	50
NVWV-M160-10	M16x1,5	10	10	37.5	41.5	9	20	50
NVWV-M160-5	M16x1,5	10	5	32.5	41.5	9	20	50
NVWV-M162-10	M16x1,5	12	10	42	46.5	9	23.5	50
NVWV-M202-10	M20x1,5	12	10	42	49	13	23.5	50
NVWV-M202-6	M20x1,5	12	6	38	49	13	23.5	50
NVWV-M207-10	M20x1,5	17	10	47	58.5	13	29.5	50
NVWV-M253-11	M25x1,5	23	11	59	67	18	37	30
NVWV-M253-7	M25x1,5	23	7	55	67	18	37	30
NVWV-M329-13	M32x1,5	29	13	68	74.5	24.5	44	20
NVWV-M329-8	M32x1,5	29	8	63	74.5	24.5	44	20
NVWV-M406-13	M40x1,5	36	13	80.5	98	30	53.5	20
NVWV-M406-8	M40x1,5	36	8	75.5	98	30	53.5	20
NVWV-M508-14	M50x1,5	48	14	95.5	111	39.5	66	10
NVWV-M508-9	M50x1,5	48	9	90.5	111	39.5	66	10
NVWV-M638-14	M63x1,5	48	14	94.5	114	50	66	10
NVWV-M638-10	M63x1,5	48	10	90.5	114	50	66	10

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö