

Female Thread Adapter Metric

- For cable protection systems in a wide range of applications.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMAFLEX conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G)
- IP68/IP69 versions are also available, contact us for more information!

Specification

MATERIAL	Polyamide PA6
INGRESS PROTECTION	IP66 stat. / IP54 dyn.
TEMPERATURE RANGE	-40°C....+105°C
COLOUR	Black RAL 9005
TEST STANDARD	EN 60529 / DIN 40050 / IEC 60529
FLAME CLASS	UL94 V0
GLOW WIRE TEST	960°C acc. to EN 60695-2-10
HALOGEN-FREE	Yes

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

ARTICLE NO.	INTERNAL THREAD	CONDUIT SIZE	L MM	H MM	E1 MM	PCS/PACK
BVID-M12MGT	M12x1,5	7	8	32.0	20	100
BVID-M160GT	M16x1,5	10	8	33.5	21.5	50
BVID-M162GT	M16x1,5	12	8	36.4	23.5	50
BVID-M207GT	M20x1,5	17	8	44.5	30	50
BVID-M253GT	M25x1,5	23	8	48.5	37	30
BVID-M329GT	M32x1,5	29	10	51.5	44	20
BVID-M406GT	M40x1,5	36	10	65.5	53.5	20
BVID-M508GT	M50x1,5	48	10	65.5	66	10
BVID-M638GT	M63x1,5	48	10	65.5	72	10

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö