



Conduit PCL - Black

Polyamide 6, standard applications

- Machine building, installation and vehicle building applications.
- High-grade, specially formulated polyamide 6
- Very good flexibility.
- Good mechanical strength at low temperatures and dry conditions.
- Temperature range -50°C ... $+105^{\circ}\text{C}$ continuous, $+160^{\circ}\text{C}$ short-term
- Self-extinguishing.
- Free from halogens and cadmium.

* lowest recommended bending radius for static (fixed) installation.

Specification

MATERIAL	Polyamide 6
TEMPERATURE RANGE	-50°C $+105^{\circ}\text{C}$
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	PROFILE	SIZE	Ø D MM	Ø D1 MM	STAT R MM*	PACKAGING TYPE	PCS/PACK
1410001	PCLT-07B.50	T	NW 7	10	6,2	15	Ring	50
1410002	PCLT-07B.K-50M	T	NW 7	10	6,2	15	Box	50
1410011	PCLT-10B.50	T	NW 10	13	9,6	20	Ring	50
1410012	PCLT-10B.K-50M	T	NW 10	13	9,6	20	Box	50
1410021	PCLT-12B.50	T	NW 12	15.8	12	30	Ring	50
1410022	PCLT-12B.K-50M	T	NW 12	15.8	12	30	Box	50
1410031	PCLT-17B.30	T	NW 17	21.2	16,2	40	Ring	30
1410032	PCLT-17B.K-30M	T	NW 17	21.2	16,2	40	Box	30
1410041	PCLG-23B.30	G	NW 23	28.5	21,9	45	Ring	30
1410042	PCLG-23B.K-30M	G	NW 23	28.5	21,9	45	Box	30
1410051	PCLG-29B.30	G	NW 29	34.5	27,6	55	Ring	30
1410061	PCLG-36B.10	G	NW 36	42.5	36,0	60	Ring	10
1410071	PCLG-48B.10	G	NW 48	54.5	47,0	70	Ring	10