



## Divisible conduit PACOF - Black

### Polyamide 6

- For rail, machine building and many other applications.
- Specially modified polyamide 6.
- Easy installation and reopening if necessary.
- Standard nominal widths can be used in combination with all standard fittings and accessories.
- Trouble-Free retrofitting.
- Applicable also for repairs.
- Self-extinguishing.
- Temperature range:  $-40^{\circ}\text{C}$  ...  $+105^{\circ}\text{C}$  continuous,  $+160^{\circ}\text{C}$  short-term.
- Very good UV resistance and weathering characteristics.
- Conforms to: EN 45545-2 HL3 (R22 & R23) and NFPA 130

\* lowest recommended bending radius for static (fixed) installation.

## Specification

<b>MATERIAL</b>	Polyamide PA6
<b>TEMPERATURE RANGE</b>	$-40^{\circ}\text{C}$ ... $+105^{\circ}\text{C}$
<b>COLOUR</b>	Black RAL 9005
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	ARTICLE NO.	SIZE	Ø D MM	Ø D1 MM	STAT R MM*	PCS/PACK
1410421	PACOF-07B.50	NW 7	10	5,6	30	50
1410422	PACOF-10B.50	NW 10	12.8	8,5	33	50
1410423	PACOF-12B.50	NW 12	15.6	11,0	35	50
1410442	PACOF-14B.50	NW 14	19	13	42	50
1410424	PACOF-17B.50	NW 17	21.1	15,5	45	50
1410443	PACOF-20B.50	NW 20	25.5	19,1	55	50
1410425	PACOF-23B.50	NW 23	28.4	22,1	70	50
1410419	PACOF-26B.50	NW 26	31.6	24,0	80	50
1410426	PACOF-29B.50	NW 29	34.5	27,2	120	50
1410427	PACOF-36B.30	NW 36	42.4	32,0	145	30
1410428	PACOF-48B.30	NW 48	54.1	43,9	150	30
PACOF-70B.10	PACOF-70B.10	NW 70	79	62.0	190	10