



Divisible conduit PPCOF - Black

Polypropylene

- For machine building and plant construction.
- Specially modified polypropylene PP.
- Can be opened and closed again in longitudinal direction any time.
- RUTAB standard nominal widths can be used in combination with all RUTAB fittings.
- Easy installation.
- Trouble-free retrofitting.
- Applicable also for repairs.
- Self-extinguishing.
- Temperature range -20°C ... $+105^{\circ}\text{C}$ continuous, $+150^{\circ}\text{C}$ short-term.

* lowest recommended bending radius for static (fixed) installation.

Specification

MATERIAL	Polypropylene
TEMPERATURE RANGE	-20°C ... $+105^{\circ}\text{C}$
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	SIZE	Ø D MM	Ø D1 MM	STAT R MM*	PCS/PACK
1410411	PPCOF-07B.50	NW 7	10	5,6	25	50
1410412	PPCOF-10B.50	NW 10	12.8	8,5	28	50
1410413	PPCOF-12B.50	NW 12	15.6	11,0	35	50
-	PPCOF-14B.50	NW 14	19	13	40	50
1410414	PPCOF-17B.50	NW 17	21.1	15,1	45	50
-	PPCOF-20B.50	NW 20	25.5	19,6	55	50
1410415	PPCOF-23B.50	NW 23	28.4	22,1	60	50
-	PPCOF-26B.50	NW 26	31.6	24,0	65	50
1410416	PPCOF-29B.50	NW 29	34.5	26,6	100	50
1410417	PPCOF-36B.30	NW 36	42.4	31,8	120	30
1410418	PPCOF-48B.30	NW 48	54.1	43,9	140	30
PPCOF-70B.10	PPCOF-70B.10	NW 70	78	60.5	200	10