
PMA EcoGuard™







BFH-RP

50% recycle based polyamide 6

PMA® EcoGuard™ BFH-RP System support

One-piece, with safety lid. Ideal for machine building, installation and construction industries.

- Quick mounting
- Fits both conduit profiles - fine (T) and coarse (G)
- Made from 50% recycle based polyamide 6.
- Temperature range –50°C ... +95°C continuous, +160°C short-term
- Very good chemical properties
- Free from halogens and cadmium
- RoHS and REACH compliant
-

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Specification

MATERIAL	Polyamide 6
TEMPERATURE RANGE	-50°C....+95°C
COLOUR	Black RAL 9005

Variants

E-NUMBER	ARTICLE NO.	CONDUIT SIZE	A MM	B MM	C MM	H MM	E MM	M	PCS/PACK
1410581	BFH-10-RP	NW 10	20.5	20	24.5	15.5	47.5	M5	100
1410582	BFH-12-RP	NW 12	24	20	27	16.5	54.5	M5	100
1410583	BFH-17-RP	NW 17	30	20	34	20	68	M6	100
1410584	BFH-23-RP	NW 23	38.5	20	42	24	85	M6	100
1410585	BFH-29-RP	NW 29	45.5	20	48	27	99	M6	100
1410586	BFH-36-RP	NW 36	55.5	20	56	31	119	M6	50
1410587	BFH-48-RP	NW 48	67.5	20	68	37	143	M6	10

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö