



Adapter cable BGPMK

Cable clamping adapters for BGPM Multiple Holders and BGPMR reduction half-shells for supporting and holding cables. Materials: High-grade, TPE. Very good UV resistance and weathering characteristics. Conforms to: EN 45545-2 HL3 (R22 & R23), NFPA 130, UL 94 (V0). Free from halogens and cadmium.

Specification

MATERIAL	TPE - Thermoplastic Elastomer
TEMPERATURE RANGE	-50°C.....+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	COMPITABLE WITH TUBE CLAMP	A MM	K MM	PCS/PACK
-	BGPMK-10/7-3	BGPM-1x10 / BGPMR-10T/17	30	BGPM/BGPMR 1 fold: 3-7mm BGPM/BGPMR 2-4 fold: 4-6mm	5
-	BGPMK-12/9-5	BGPM-Xx12 / BGPMR-12T/17	30	BGPM/BGPMR 1 fold: 5-9mm BGPM/BGPMR 2-4 fold: 6-8mm	5
-	BGPMK-17/12-8	BGPM-Xx17 / BGPMR-17GT/23	30	BGPM/BGPMR 1 fold: 8-12mm BGPM/BGPMR 2-4 fold: 9-11mm	5
-	BGPMK-17/15-11	BGPM-Xx17 / BGPMR-17GT/23	30	BGPM/BGPMR 1 fold: 11-15mm BGPM/BGPMR 2-4 fold: 12-14mm	5
-	BGPMK-23/18-14	BGPM-Xx23 / BGPMR-23GT/29	30	BGPM/BGPMR 1 fold: 14-18mm BGPM/BGPMR 2-4 fold: 15-17mm	5
-	BGPMK-23/20-16	BGPM-Xx23 / BGPMR-23GT/29	30	BGPM/BGPMR 1 fold: 16-20mm BGPM/BGPMR 2-4 fold: 17-19mm	5
-	BGPMK-29/22-18	BGPM-Xx29 / BGPMR-29GT/36	30	BGPM/BGPMR 1 fold: 18-22mm BGPM/BGPMR 2-4 fold: 19-21mm	5
-	BGPMK-29/25-21	BGPM-Xx29 / BGPMR-29GT/36	30	BGPM/BGPMR 1 fold: 21-25mm BGPM/BGPMR 2-4 fold: 22-24mm	5
1406555	BGPMK-36/28-24	BGPM-Xx36 / BGPMR-36GT/48	30	BGPM/BGPMR 1 fold: 24-28mm BGPM/BGPMR 2-4 fold: 25-27mm	5
-	BGPMK-36/31-27	BGPM-Xx36 / BGPMR-36GT/48	30	BGPM/BGPMR 1 fold: 27-31mm BGPM/BGPMR 2-4 fold: 28-30mm	5
1406554	BGPMK-36/34-30	BGPM-Xx36 / BGPMR-36GT/48	30	BGPM/BGPMR 1 fold: 30-34mm BGPM/BGPMR 2-4 fold: 31-33mm	5
-	BGPMK-48/37-33	BGPM-Xx48	30	BGPM/BGPMR 1 fold: 33-37mm BGPM/BGPMR 2-4 fold: 34-36mm	5
-	BGPMK-48/40-36	BGPM-Xx48	30	BGPM/BGPMR 1 fold: 36-40mm BGPM/BGPMR 2-4 fold: 37-39mm	5
-	BGPMK-48/43-39	BGPM-Xx48	30	BGPM/BGPMR 1 fold: 39-43mm BGPM/BGPMR 2-4 fold: 40-42mm	5
-	BGPMK-48/46-42	BGPM-Xx48	30	BGPM/BGPMR 1 fold: 42-46mm BGPM/BGPMR 2-4 fold: 43-45mm	5