



## BSSK

### Used in combination with BSH tube clamps

- Ball-joint half shells providing additional freedom of movement for corrugated conduits fixed in BSH automation tube clamps
- Used in combination with BSH tube clamps
- Increases freedom of movement for conduits
- Optimum solution for cable guidance in automation applications
- Extends lifetime of conduit and cables due to reduced mechanical stress
- Easy to install and exchange
- High-grade, specially formulated polyamide 6
- Free from halogens and cadmium

Compatible with:

- PMA Automation BSH Tube clamp
- PMAFLEX Pro Conduits
- PMAFLEX Multilayer Conduits
- PMAFLEX Conduits

## Specification

<b>MATERIAL</b>	Polyamide PA6
<b>TEMPERATURE RANGE</b>	-45°C...+105°C
<b>COLOUR</b>	Black RAL 9005
<b>HALOGEN-FREE</b>	Yes

## Variants

E-NUMBER	ARTICLE NO.	CONDUIT SIZE	COMPITABLE WITH TUBE CLAMP	A MM	D1 MM	PCS/PACK
1410496	BSSK-23GT	NW 23	BSH-R23	27	42.2	30
-	BSSK-29GT	NW 29	BSH-R29	28	48.1	20
-	BSSK-36GT	NW 36	BSH-R36	30	55	20
-	BSSK-48GT	NW 48	BSH-R48	30	65.9	10
-	BSSK-56G	NW 56	BSH-R56	34	80.9	10