



Slide insert BGN

Used in combination with BSH tube clamps

- Sliding bush for automation applications.
- High-grade, specially formulated polyamide 6.
- Used in combination with hose clamps BSH (eg BSH-RXX).
- Allows axial movement of the protective tubing to avoiding torsion.
- Free from halogens and cadmium.

Specification

INFORMATION_KLIKSEAL

Slide insert for use in automation applications.
To be used in combination with tube clamp BSH (for example BSH-RXX).
Allows axial movement of the conduit to reduce stress.
Material: specially formulated polyamide 6.
Free from halogen and cadmium.

MATERIAL	Polyamide 6
TEMPERATURE RANGE	-40°C....+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	CONDUIT SIZE	COMPITABLE WITH TUBE CLAMP	A MM	B MM	C MM	D MM	PCS/PACK
1410456	BGN-R29	NW 29 T+G-profile	BSH-R29	26	34	41	47	30
1410457	BGN-R36	NW 36 T+G-profile	BSH-R36	26,5	36	49	55	20
-	BGN-R36/48	NW 36 T+G-profile	BSH-R48	26,5	34	60	66,5	20
1410458	BGN-R48	NW 48 T+G-profile	BSH-R48	26	36,5	60,5	66,5	20
1410459	BGN-R56	NW 56 G-profile	BSH-R56	30	38	75	81	10
-	BGN-R56S/70	NW 56 G-profile	BSH-R70	40	45	94,5	103,5	10
1410461	BGN-R70	NW 70 G-profile	BSH-R70	40,5	45	97,5	105	10