



## Tube Clamp BSH

- For automation applications, guiding or fixing PMA conduits.
- High-grade, specially formulated polyamide 6.
- Single-piece, robust construction.
- Easy installation.
- To be used in combination with standard half shells GN.
- Space saving design allows optimum installation in automation applications.
- Extends lifecycle of the cable pack due to reduced mechanical stress (avoiding torsion).
- Free from halogens and cadmium

## Specification

Tube clamp for use in automation applications for guiding or fixing conduits.

Tube clamp BSH to be used in combination with standard half-shells (slide inserts or strain relief inserts, (for example BGN-RXX/BGN-SXXX).

Material: high grade, specially formulated polyamide 6.

Single-piece, robust construction.

Easy installation.

To be used in combination with standard half-shells GN.

Space saving design allows optimum installation in automation applications.

Extends lifecycle of the cable pack due to reduced mechanical stress (avoiding torsion).

Free from halogens and cadmium.

### INFORMATION\_KLIKSEAL

|                          |                 |
|--------------------------|-----------------|
| <b>MATERIAL</b>          | Polyamide 6     |
| <b>TEMPERATURE RANGE</b> | -40°C....+105°C |
| <b>COLOUR</b>            | Black RAL 9005  |
| <b>HALOGEN-FREE</b>      | Yes             |

## Variants

| E-NUMBER | ARTICLE NO. | A MM  | B MM | C MM | D MM | H MM  | E MM | Ø ID MM | PCS/PACK |
|----------|-------------|-------|------|------|------|-------|------|---------|----------|
| 1410468  | BSH-R23     | 64    | 26   | 30   | -    | 60,5  | 34   | 34,9    | 30       |
| 1410451  | BSH-R29     | 71    | 26   | 30   | -    | 67    | 34   | 41      | 30       |
| 1410452  | BSH-R36     | 81.5  | 26   | 30   | -    | 77.5  | 36   | 49      | 20       |
| 1410453  | BSH-R48     | 96    | 26   | 30   | -    | 91    | 36.5 | 61      | 20       |
| 1410454  | BSH-R56     | 112.5 | 30   | 60   | 30   | 109.5 | 38   | 75.5    | 20       |
| 1410455  | BSH-R70     | 149   | 40   | 60   | 30   | 144   | 45   | 98      | 20       |