



Tube Clamp BSH

- For automation applications, guiding or fixing PMA conduits.
- High-grade, specially formulated polyamide 6.
- Single-piece, robust construction.
- Easy installation.
- To be used in combination with standard half shells GN.
- Space saving design allows optimum installation in automation applications.
- Extends lifecycle of the cable pack due to reduced mechanical stress (avoiding torsion).
- Free from halogens and cadmium

Specification

MATERIAL	Polyamide 6
TEMPERATURE RANGE	-40°C....+105°C
COLOUR	Black RAL 9005
HALOGEN-FREE	Yes

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

E-NUMBER	ARTICLE NO.	A MM	B MM	C MM	D MM	H MM	E MM	Ø ID MM	PCS/PACK
1410468	BSH-R23	64	26	30	-	60,5	34	34,9	30
1410451	BSH-R29	71	26	30	-	67	34	41	30
1410452	BSH-R36	81.5	26	30	-	77.5	36	49	20
1410453	BSH-R48	96	26	30	-	91	36.5	61	20
1410454	BSH-R56	112.5	30	60	30	109.5	38	75.5	20
1410455	BSH-R70	149	40	60	30	144	45	98	20

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö